


- NOTES:**
- VOLTAGE MAY VARY WITH CONTROL SETTING
  - LINE VOLTAGE MAINTAINED BY 120VAC, 50/60HZ
  - ALL DC VOLTAGES 10% MEASURED FROM POINT INDICATED TO CHASSIS USING HIGH IMPEDANCE METER WITH NO SIGNAL INPUT. CONTRAST AND BRIGHTNESS CONTROLS AT MAXIMUM. ALL OTHER CONTROLS IN NORMAL OPERATING POSITION
  - WITH INTERNAL NUMBER INDICATES LOCATION OF WAVE FORM READING
  - M - INDICATES RESISTORS LOCATED IN PICTURE TUBE LEAD ASSEMBLY
  - RESISTANCE VALUES IN OHMS, 1/2 WATT, 10% UNLESS OTHERWISE NOTED. K=1,000 M=1,000,000
  - CAPACITANCE VALUES OF 1 OR LESS ARE IN MICROFARADS, ABOVE 1 IN PICOFARADS UNLESS OTHERWISE NOTED.
  - PRODUCT SAFETY NOTICE: PARTS IDENTIFIED BY SHADING ARE SAFETY CRITICAL COMPONENTS. REPLACE ONLY WITH SAME TYPE PARTS SHOWN IN PARTS LIST.



# WELLS - GARDNER ELECTRONICS CORPORATION

2701 N. KILDARE AVE. • CHICAGO, ILL. 60639 • ALBANY 2-8220  
TELEX 25-3286

**IN COCKTAIL TABLE MODEL**

V1002-5770